MUASSILO

ITR-1345 199 A Copy No.

PRELIMINARY REPORT (No WT Issoed) peration


EDWING.

PROVING

May - July 1956
Classification (Canoolica) (Changed to
By Authority of DASASC-3 memo


GAMMA RAYS FROM PLANE AND VOLUME SOURCE DISTRIBUTIONS

19960702 081



BTAIBUTION BTATEMENT A

Approved for public release Diamounen Unimited



HEADQUARTERS FIELD COMMAND, ARMED FORCES SPECIAL WEAPONS PROJECT SANDIA BASE. ALBUQUERQUE. NEW MEXICO

DECLASSIFIED BY DNA ISTS PER NTPR REVIEW. DISTRIBUTION STATEMENT "A"

DATE 10/20/95



DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.



Defense Nuclear Agency 6801 Telegraph Road Alexandria, Virginia 22310-3398



ISST

29 January 1996

MEMORANDUM FOR DEFENSE TECHNICAL INFORMATION CENTER ATTENTION: OCD/Mr. Bill Bush

SUBJECT: Declassification of ITR-1345

The Defense Nuclear Agency Security Office (OPSSI) has declassified the following report:

ITR-1345
Preliminary Report
Operation REDWING
Pacific Proving Grounds
May-July 1956
Gamma Rays From Plane and Volume Source
Distributions.

Distribution statement "A" applies.

Since this report does not have a final issue, this office has enclosed a copy for NTIS' system. Please inform DNA of the assigned accession number.

Enclosure:

A/S

JOSEPHINE B. WOOD

Chief, Technical Support Branch

INCLASSITION

This is a preliminary report based on all data available at the close of this project's participation in Operation REDWING. The contents of this report are subject to change upon completion of evaluation for the final report. This preliminary report will be superseded by the publication of the final (WT) report. Conclusions and recommendations drawn herein, if any, are therefore tentative. The work is reported at this early time to provide early test results to those concerned with the effects of nuclear weapons and to provide for an interchange of information between projects for the preparation of final reports.

When no longer required, this document may be destroyed in accordance with applicable security regulations. When destroyed, notification should be made to

AEC Technical Information Service Extension
P. O. Box 401
Oak Ridge, Tenn.

DO NOT RETURN THIS DOCUMENT

MARINED



ITR-1345

This document consists of 38 pages No. 159 of 265 copies, Series A

OPERATION REDWING - PRELIMINARY REPORT SEPTEMBER 1956

GAMMA RAYS FROM PLANE AND VOLUME SOURCE DISTRIBUTIONS

Victor A. J. van Lint

Approved:

Program 2 Staff Weapons Effects Tests Armed Forces Special Weapons Project LL Woodward
Sandia Rese Field Command Sandia Base Albuquerque, New Mexico

L. L. Woodward, Col, USAF

Hemmeth D. Coleman

- Maring

Technical Director

K. D. Coleman, Col, USAF Commander, Task Unit 3

D. C. Campbell, CDR, USN Director, Program 2




SUMMARY OF SHOT DATA, OPERATION REDWING

Shot Name	Date	Time	Location	Туре	H&N Coordinates (Actual Ground Zero)	Geographic
(Unclassified)	(PPC)	(approximates)				# - 0
Lacrosse	5 May	6290	Enlustok Yvorne	Surface Land	124,515 E 106885 N	11 33 29
Cherokee	21 May	T550	Bildni Off Charlie	Air Drop (4320:150 ft) Over Weter	96200 ± 100 E 185100 ± 500 N	11 43 50
Zund	28 May	9550	Hich	Surface Land Water	110309 E 100154 N	11 29 48
Yume	28 May	9510	Entwetok	200-ft Towar	112155 E 130604 N	11 37 24 162 19 13
Erie	31 May	0615	Eniwetok Yvome	300-ft Tower	127930 E 102060 II	11 32 41
Semtnole	6 June	1255	Eniwatok Irene	Surface Land ^a	7537 E 149897 K	11 40 35 162 13 02
Flathead	12 June	9290	Bikini Off Dog	Darge Water	116768 E 164094 N	165 23 U
Blackfoot	12 June	9290	Entwetok Yome	200-ft Tower	126080 E 104435 N	11 33 04
Kickapoo	14 June	325	Endwetok Sally	300-ft Tower	132295 N	11 37 41 162 19 32
Osago	16 June	7374	Enivetok Yvome	Air Drop (680±35 ft) Over Land	126647 ± 50 E 102851 ± 50 N	162 21 39
Eod.	22 June	9560	Eniwetok Pearl	200-ft Towar	105300 E 133540 N	11 37 53
Dakota	26 June	9090	Bikini Off Dog	Barge	116767 E 164,097 N	11 40 22 165 23 13
Nobavk	3 July	9090	Eniwetok Ruby	300-ft Tower	109737 E 132165 N	11 37 39
Apache	9 July	9090	Entwetok Flora	Barge Nater	69227 E 148063 N	11 40 17
Navajo	עלטיל בנ	0556	Bildrd Off Dog	Barge Water	116816 E 160604 II	11 39 48
Town .	21 July	9750	Bikini Charlio-Dog Reef	Barge Water	99776 Е 164476 н	11 40 26
Huron	22 July	9190	Entwetok	Barge Water	70015 E 148304 H	11 40 19


ase ITR-1344 for further details.

Milhoung 11


Und hand had







Bikini Atoll. Locations of test detonations during Operation REDWING are indicated by large lettering and arrows. Native island names with corresponding military identifiers are given in the tabulation.



Eniwetok Atoll. Locations of test detonations during Operation REDWING are indicated by large lettering and arrows. Native island names with corresponding military identifiers are given in the tabulation.



ABSTRACT

Calculations have been performed for the gamma-ray dose rate: (1) inside a uniformly contaminated volume, as in a radioactive cloud or in contaminated water; (2) as a function of altitude above the center of a uniformly contaminated circular island; and (3) as a function of altitude above uniformly contaminated water.

The calculations have been performed for monoenergetic sources of 0.15, 0.30, 0.60, 1.2, and 2.5 Mev and for some experimentally observed

fallout spectra.

FOREWORD

This report presents the results of a special study undertaken in connection with the fallout program of Operation REDWING to provide a theoretical basis for analysis of the experimental results of Projects 2.61 through 2.66. Since a field instrumentation effort was not involved, this report does not carry a project number, and will not be

replaced by a WT-series final report.

For readers interested in other pertinent test information, reference is made to ITR-1344, Summary Report of the Commander, Task Unit 3. This summary report includes the following information of general interest: (1) an overall description of each detonation, including yield, height of burst, ground zero location, time of detonation, and ambient atmospheric conditions at detonation; (2) a discussion of all project results; (3) a summary of each project, including objectives and results; and (4) a complete listing of all reports covering the Military Effects Program.

CONTENTS

ABSTRAC FOREWOR		:	•	•	•	•	•	•	•	•	:	•	•	•	•	` 5 6
CHAPTER	1	INT	RODU	CTION		•	•				•	•	•	•	•	9
CHAPTER 2.1 2.2 2.3	- In	t.ere.	でももの	HEORY ns of n of I	Com	ma De	Darro					•	•	•	•	10 10 10
3.2	Do	se Ra se Ra	ate :	S. in an Above in Air	Cent	ter d	Med of Ci	ircul	lar 1	Disk Wate	•		•	•	•	14 14 15 17
CHAPTER	4	REST	MIS	OF CA	TCU	ATIO	ONS	•	•	•	•	•	•	•	•	20
CHAPTER	5	DISC	russi	CON	•	•	•	•	•	•	•	•	•	•	•	34
REFEREN	CES	•	•	•	•	•	•	• .	•	•	•	•	•	•	•	35
3.1 4.1 4.2		atter Sumed	red E l Spe se Co	hergy ectra nvers	Flu	ix Fr Fact	racti	ions,	s _i	•		•	•	•	•	17 20 21
FIGURES 2.1	Bui	lldur	fac	tor c	oeff	icie	ents		•					_		12
4.5	Hei Hei Hei Hei Hei Hei	ight ight ight ight ight ight ight	conv conv conv conv conv	rersio rersio rersio rersio rersio rersio rersio facto	n fe n fa n fa n fa n fa n fa n fa	etor etor etor etor etor etor	vo and vo	ver 1	and and and and and and and	E E E E S S S S	= = = = ect	rum rum	Mev Mev Mev Mev I.	•		22 23 24 25 26 27 28 29
	pla	me -	mon	oener	geti	c so	urce	s	•	•	•		•		•	30

	Conversion factors from finite to infinite					
	plane. Spectrum I, II, and III		•	•	•	31
4.11	Height conversion factors over water -					
	monoenergetic sources	•	•	•	•	32
4.12	Height conversion factors over water.					
	Spectrum T. TT. and TTT.				•	33



CHAPTER 1

INTRODUCTION


There are two basic techniques for a field determination of the distribution of radioactive emitters in a medium: (1) securing samples of radioactive material from various portions of the medium and analyzing these samples with standard laboratory counting equipment and (2) making a radiation survey near the actual distribution of emitters. The first technique is the more accurate, but it involves long time delays associated with careful collection of samples, transportation to a laboratory, and subsequent standard geometry counting. The survey technique has been applied extensively during tests of nuclear sapons to the problem of delineating fallout areas on land and determining contamination levels for Radiological Safety purposes. It has also been applied to determine the distribution of radioactive material in the ocean and in the radioactive cloud following a nuclear detonation.

The purpose of the calculations which follow is to establish the relation between the gamma dose rate measured by a survey reading at a specified location and the density of radioactive emitters in the assumed distribution. In this presentation the dose rate will be defined as the radiation field measured in r/hr - namely, the ionization per unit volume of STP air. The actual situations under which such measurements are performed can be approximated by three ideal cases in which the dose rate is taken: (1) within an infinite medium uniformly populated with radioactive sources; (2) above the center of a circular disk containing a uniform surface distribution of sources; or (3) in a semi-infinite medium at various distances from the interface with the complementary semi-infinite medium, having a different composition, which has radioactive sources uniformly distributed throughout its volume.

The first case corresponds to the measurement of the dose rate within a nuclear cloud or within water in which radioactive fallout has been mixed. The second applies approximately to the problem of determining the contamination of the surface of an island by a measurement of the dose rate above its center. The large land-source problem is that in which the radius of the disk is allowed to become infinite. The third case corresponds to the measurement of the dose rate in the air above contaminated ocean water.

The actual calculations are performed for the following monoenergetic sources: 150 kev, 300 kev, 600 kev, 1.2 Mev, and 2.5 Mev. The data which may then be used to compute the absorption relations for any spectrum, are applied to some experimentally observed fallout spectra.





CHAPTER 2

BASIC THEORY

2.1 INTERACTIONS OF GAMMA RAYS

Gamma rays of moderate energy interact with matter by the follow-

ing three mechanisms:

1. Photoelectric Absorption. The gamma ray ejects an electron from an atom, imparting its total energy to the electron. The gamma ray disappears, and the energy is locally distributed by ionizing and exciting collisions of the electron.

2. Compton Scattering. The gamma ray imparts a portion of its energy to an electron and a scattered gamma ray of lower energy travels in a new direction. The energy of the electron is locally distributed, but the scattered gamma ray contributes to the resultant gamma dosage elsewhere.


3. Pair Production. A high-energy (>1.02 Mev) gamma ray can interact with an electric field to produce an electron-positron pair. The gamma ray disappears, and the kinetic energy of the electron and positron are locally distributed. The subsequent annihilation of the positron produces two gamma rays of 0.511-Mev energy which travel in opposite but arbitrary directions and contribute to the total gamma dosage elsewhere.

Each of the above interactions has a certain probability (μ_1, μ_2, μ_3) of occurring per unit path length of a gamma ray in a given medium. The probability that any of the interactions occurs per unit path length is then $\mu_0 = \mu_1 + \mu_2 + \mu_3$ and the probability that the gamma ray has not interacted in a distance $X = e^{-\mu_0 X}$.

2.2 CALCULATION OF DOSE RATE

The dose rate at a particular point in a radiation field is defined as the number of ion pairs produced per unit volume of air (STP) located at that point. The number of ion pairs produced is proportional to the energy lost per unit volume. Therefore, if the flux of particles of

Defined as the number of gammas per unit time crossing a unit area perpendicular to their direction of motion.



energy E_o at the point is F_o and the average fraction of the energy lost per unit distance is h_o , then the dose rate (in r/hr) is:

$$D_{o} = C E_{o} h_{o} F_{o}$$
 (2.1)

Where: C = 0.058; factor to convert from energy (Mev) deposited per unit volume (cm³) per second to roentgens per hour.

2.3 DOSE BUILDUP

th

ot

be.

ed

e.

The dose rate at a distance R due to the unscattered flux from a monoenergetic point source of radiation emitting Ao photons per unit time can be calculated to be:

$$D_{ou} = C E_o h_o \frac{A_o}{\Delta \pi R^2} e^{-\mu_o R}$$
 (2.2)

However, the dose rate is augmented by the contribution of the scattered photons. The magnitude of this dose-rate buildup has been computed for some special cases (Reference 1). The buildup factor in air has been graphed as a function of energy for various source energies (Reference 2). For the purposes of the mumerical calculations involved in this report, principally to avoid tedious numerical integrations, these curves have been approximated by cubic equations:

$$B_0 = 1 + b_0 (\mu_0 R) + c_0 (\mu_0 R)^2 + d_0 (\mu_0 R)^3$$
 (2.3)

The coefficients have been graphed as a function of source energy E_0 (Figure 2.1).

It will be assumed that these same coefficients apply in the case of water, since the density effect is incorporated into μ_0 and the mean atomic number is not greatly different from that of air.

The foregoing buildup factors were calculated ones and include contributions from the entire gamma spectrum below E₀. However, actual survey instruments usually do not detect radiation below a certain energy, usually 60 to 75 kev. Therefore, the fraction of the scattered dose contributed by such low-energy gammas was estimated using the curves in Reference 1, and this amount was subtracted from the calculated dose rate. Effectively, this procedure amounted to multiplying bo, c₀, and d₀ by a factor less than one representing the fraction of the scattered dose contributed by detectable gammas.

During the solution of Case 3, it is necessary to evaluate the actual scattered flux penetrating the interface, rather than the dose rate. The curves presented in Reference 1 were again used to convert the scattered dose rate to flux as a function of energy. The method

 $h_0 = \mu_1 + f_2\mu_2 + f_3\mu_3$ where f_2 and f_3 are the average fractions of the initial energy deposited locally for Compton scattering and pair production, respectively.




Figure 2.1 Buildup factor coefficients.

$$B_0 = 1 + b_0(\mu_0 R) + c_0(\mu_0 R)^2 + d_0(\mu_0 R)^3$$

used was to approximate the scattered spectrum by a sum of monoenergetic sources of energies 0.15, 0.30, 0.60, 1.2, and 2.5 MeV, where the relative strengths of these sources were determined by evaluating areas under the energy-flux curves of Reference 1. For this purpose the variation of h with energy was neglected, since it does, in fact, deviate from an average value, h, by less than 15 percent.


CHAPTER 3

FORMULAS

3.1 DOSE RATE IN AN INFINITE MEDIUM

The dose rate at P due to a monoenergetic volume density of activity, A_{VO}, at (R, θ , ϕ) is:

$$dD_{0} = \underbrace{\frac{B_{0}(\mu_{0}R)}{dose}}_{\begin{array}{c} c \ E_{0} \ h_{0} \\ \\ buildup \end{array}} \underbrace{\frac{C \ E_{0} \ h_{0}}{dose}}_{\begin{array}{c} c \ E_{0} \ h_{0} \\ \\ \hline \end{array}} \underbrace{\frac{R^{2} \ sin \ \theta \ d\theta d\phi \ dR}{volume}}_{\begin{array}{c} c \ E_{0}R \\ \\ \hline \end{array}} \underbrace{\frac{1}{4\pi R^{2}}}_{\begin{array}{c} c \ E_{0}R \\ \\ \hline \end{array}} \tag{3.1}$$



Inserting the assumed cubic equation for the buildup factor and integrating over all space variables, the total dose rate is derived to be:

$$D_o = C E_o h_o \frac{A_{vo}}{\mu_o} (1 + b_o + 2c_o + 6d_o)$$
 (3.2)

When the sources emit a spectrum of gamma rays, the above dose rate must be integrated over the energy spectrum.

3.2 DOSE RATE ABOVE CENTER OF CIRCULAR DISK


LV-

3.1)

The dose rate at point P due to a monoenergetic uniform surface density, A_{so} , of isotropic sources at (R,ϕ) is:

$$dD_{o} = B_{o}(\mu_{o}R) \quad C E_{o} h_{o} \quad A_{so} \quad R dR d\phi \quad e^{-\mu_{o}R} \quad \frac{1}{4\pi R^{2}}$$

$$(3.3)$$



If the sources of the radiation do not emit isotropically, the quantity $\frac{A_{so}}{4\pi}$ should be replaced by the number of photons emitted per unit time, per unit surface area, per unit solid angle in the particular direction.

For isotropic emitters, the dose rate integrated over ϕ and up to the edge of a disk of radius ρ is:

$$D_{o}(Z,\rho) = C E_{o} h_{o} \frac{A_{so}}{2} \left[K(\mu_{o}Z) - K(\mu_{o}\sqrt{Z^{2} + \rho^{2}}) \right]$$
(3.4)

Where:
$$K(X) = \mathcal{E}_{i}(-X) + e^{-X} \left[(b_{o} + c_{o} + 2d_{o}) + X (c_{o} + 2d_{o}) + X^{2} d_{o} \right]$$

$$-\mathcal{E}_{i}(-X) = \int_{X}^{\infty} \frac{e^{-t}}{t} dt, \text{ is the usual exponential integral.}$$

For heights large compared to the radius of the source field $(Z>>\rho)$, this formula approaches the formula for a point source having the full strength of the disk at a distance Z, namely:

$$D_{o}(Z_{\bullet}\rho)_{\overline{Z}>>\rho}$$
 $C E_{o} h_{o} \frac{A_{so}\rho^{2}}{4 Z^{2}} e^{-\mu_{o}Z} \left[1 + b_{o}(\mu_{o}Z) + \frac{A_{so}\rho^{2}}{2}\right]$

$$c_o(\mu_o Z)^2 + d_o(\mu_o Z)^3$$
 (3.5)

One interesting and useful result demonstrated by the above derivation is related to the fact that the two K factors are functions of the slant range to the near and far points of the contaminated circle and do not depend on any other distance. In particular, a calculation of the dose rate on the surface at the center of an uncontaminated circle of radius ρ amidst an infinite contaminated plane yields the same answer as the dose rate at a height ρ above an infinite contaminated plane, since both are proportional to K $(\mu_0 \rho)$.

The foregoing solution actually corresponds to a contaminated plane in an infinite isotropic medium and thus differs slightly from the groundair problem in which the medium does differ on the two sides of the plane. This fact affects the dose rate in the air through two mechanisms: (1) the effective atomic number of the ground is somewhat different from that of the air; therefore, the absorption and scattering cross sections are different and (2) the scale of the scattered trajectories is foreshortened by the greater density of the soil and thus affects the dose rate for finite-size source fields. Actually the error caused by the isotropic-medium assumption is probably less than 15 percent.

The fact that the above formula becomes logarithmically infinite as the detector approaches the surface is associated with the mathematical assumption that the vertical dimension of the detector is small compared to its distance from the plane; hence, a finite number of sources are at distance zero from the detector.

3.3 DOSE RATE IN AIR ABOVE CONTAMINATED WATER

The solution of the air-above-water problem is performed in two steps: (1) the method of Section 3.1 is utilized to calculate the flux crossing the water surface and (2) this flux is inserted into the differential formula of Section 3.2 to calculate the effect of the air absorption.

In both steps of this solution the same assumption as that discussed in Section 3.2 must be made, i.e., the dose-buildup characteristics in a semi-infinite medium bounded by another different semi-infinite medium are the same as in a homogeneous infinite medium. In this case the errors should be small, because the effective atomic number of air and water differ but slightly and there is almost always an essentially infinite boundary surface between.

Since the effective atomic numbers do not differ greatly, the further assumption will be made that the same dose-buildup coefficients can be applied to both media. Actually, the quantity desired from the water calculation is the flux as a function of energy - not the total dose rate. Therefore, the scattered dose rate must be allocated according to the energy spectrum of the scattered radiation. In the more-general problem, where the sources emit a spectrum of gamma rays, this calculation can be represented as a modification to the primary energy spectrum.

TABLE 3.1 SCATTERED ENERGY FLUX FRACTIONS, 8;

Escat (Mev)	0.15	0.3	0.6	1.2	2.5	<0.75
E _o (Mev)						۶
0.15 0.3 0.6 1.2 2.5	0.15 0.55 0.25 0.20 0.10	0.20 0.30 0.20 0.10	0.25 0.25 0.15	0.25 0.35	0.25	0.85 0.25 0.20 0.10 0.05

The curves in Reference 1 have been used to allocate this dose rate among the various contributing energies. The energy-flux curves have been separated into intervals centered at a series of energies Eo, Eo/2, Eo/4, Eo/8, etc., with the lowest interval bounded by 75 kev. For the purpose of these calculations, the average fractional energy loss, h, is assumed to have a constant value of $\bar{h}=0.33~\mathrm{X}~10^{-4}\mathrm{cm}^{-1}$ over the entire range; therefore, the area under the energy-flux curves within each of the intervals measures their relative contributions to the scattered dose rate. The fraction of the total scattered flux contributed by each energy, si, computed in this manner is given in Table 3.1. Again, the part below 75 kev will be ignored, since instruments will not be sensitive to it.

ng

.4)

:.5)

W8he

ane

oundlane. 1)

.ons

e

1 85 al

red

In the ensuing calculations, the scattered flux has been reintroduced as an effective uniformly distributed additional source such that only the unscattered flux from the composite source need be calculated. In other words, the flux at the surface will be correctly evaluated by calculation of the unscattered radiation from the composite source distribution. From formulas derived before, the additional source strength at E_i due to a source of strength A_{vo} at E_0 is:

$$\triangle A_{vi} = s_i \frac{E_o}{E_i} \frac{\mu_i}{\mu_o} \frac{h_o}{\overline{h}} A_{vo} (b_o + 2c_o + 6d_o)$$
 (3.6)

The effective source strength A_{vj}^* at energy E_j can then be calculated by adding the real source, A_j , to all terms ΔA_{vj} due to primary source of energy $E_0 \ge E_i$.

The angular distribution of the scattered radiation will be assumed to be the same as that of the unscattered radiation, since this corres-

ponds to isotropy in the upper hemisphere.

Using the method of Section 3.1, the number of unscattered photons due to a source A_{VO}^* per unit time crossing a unit surface area at an angle θ is:

$$A_{o}(\theta) d\Omega = \int_{-4\pi}^{\infty} \frac{A_{vo}^{*}}{4\pi} e^{-\mu_{ov}R} \cos \theta dR d\Omega$$

$$R = 0$$

$$= \frac{A_{vo}^{*}}{4\pi\mu_{ov}} \cos \theta d\Omega \qquad (3.7)$$

Where: μ_{ow} = Interaction coefficient of water for gammas of energy E_{o} .

The factor $\cos\theta$ arises from the fact that a unit area of the surface projects onto an area $\cos\theta$ perpendicular to the direction of flight of the photons.

As indicated in Section 3.2, quantity $A_0(\theta)$ is to be inserted instead of $\frac{A_{SO}}{A_{SO}}$ in the differential form of the infinite plane formula.

Inis expression must be inserted into the differential formula because the angular dependence of the radiation coming through the surface differs from the contaminated plane case by a factor $\cos \theta$.

$$D_{o}(Z) = \int_{0}^{\infty} \int_{0}^{2\pi} B_{o}(\mu_{o}R) C E_{o} h_{o} \frac{A_{vo}^{*}}{\mu_{ow}} \frac{Z_{o}}{R} \frac{e^{-\mu_{o}R}}{4\pi R^{2}} R d\phi dR$$

$$= C E_{o} h_{o} \frac{A_{vo}^{*}}{2\mu_{ow}} K_{w} (\mu_{o}Z)$$
(3.8)

Where:
$$K_W(X) = X \mathcal{E}_1(-X)$$
 $(1-b_0) + e^{-X} \left[1 + X (c_0 + d_0) + X^2 d_0 \right]$

.6)

æ

ned

38

of

use

This dose-rate expression must subsequently be summed over the effective source-energy spectrum, $A_{\rm Vi}^{\rm x}$, to obtain the total dose rate. The above expression does not approach infinity as the detector approaches the interface, since the volume distribution of sources places only an infinitesimal number of them at distance zero from the detector.

If a detector having a sensitive solid angle less than 2π is used, a finite circle becomes the effective source, and the above integral should be taken to the finite upper limit $L = \frac{Z}{\cos \alpha}$, where α is the acceptance angle of the detector. The finite field $K_{\rm wf}$ factor is then given by the following expression:

$$K_{\text{wf}} (\mu_{\text{o}} Z, \alpha) = K_{\text{w}} (\mu_{\text{o}} Z) - \cos \alpha K_{\text{w}} \left(\frac{\mu_{\text{o}} Z}{\cos \alpha}\right)$$
 (3.9)

CHAPTER 4

RESULTS OF CALCULATIONS

Calculations have been performed for monoenergetic sources of 0.15, 0.30, 0.60, 1.2, and 2.5 Mev. In addition, they have been performed for three particular gamma-ray-source spectra applicable to radioactive fallout fields resulting from nuclear detonations. The composition of these spectra in terms of the calculated energies is summarized in Table 4.1. They are applicable to: (1) fission-product activity from a fission weapon, (2) early (one-day) activity from a thermonuclear weapon, and (3) later (2-to-7-day) activity from a thermonuclear weapon.

TABLE 4.1 ASSUMED SPECTRA

E _o (Mev)		Relative Photon Flux Fercent					
	Spectrum I	Spectrum II	Spectrum III				
0.45 0.3 0.6 1.2 2.5	15 20 45 15 5	25 25 24 24 24 2	50 25 20 4 1				
Average Energy	0.66 Nev	0.59 Mev	0.34 Nev				

Table 4.2 summarizes the absolute conversion factors derived from these calculations. The surface or volume density of activity is chosen to be one curie per square meter or cubic meter, respectively.

Figures 4.1 through 4.8 present the factor to convert a reading at a height Z above a finite contaminated plane to a reading at a height of 3 feet. Figures 4.9 and 4.10 present the conversion of the 3-foot reading from a finite-plane source to an infinite-plane source having the same surface density of activity.

Figures 4.11 and 4.12 present the altitude conversion factors for the air-over-water case.

TABLE 4.2 ABSOLUTE CONVERSION FACTORS

Eo	In sector of 1 curio/neces 1		Infinite Volume Distribution in Air of 1 curie/meter3	Infinite Surface Distribution of 1 curie/meter ²				
	Dose Rate in Water	Dose Rate at 3 ft Above Water	Dose Rate in Air	Dose Rate at 3 ft Above Surface				
Mev	r/hr	r/hr	r/hr	r/hr x .39				
0.15 0.3 0.6 1.2 2.5	0.104 0.60 1.25 2.58 5.37	0.05 0.29 0.61 1.28 2.67	96 6 55 554 1160 1945 2360 1970 5040	1.95 .75 6.05 2.32 12.1 J 22.0 4.5 39.8 15.3				
III II	1.36 1.19 0.60	0. <i>67</i> 0. <i>5</i> 9 0. <i>2</i> 9	1250 1110 560	12.2 4.44 10.6 4.67 6.2 3.55				

^aDistances large compared to $1/\mu_0$.

1.03 .51

2.60 x 10 0 cm = =

- m/medie

n sen

15, for

£

1 a on,

at of2d-

r




Figure 4.1 Height conversion factors over land. $E_{\rm o}=0.15~{\rm Mev}$. (Numbers on curves refer to radius of source circle in feet)




Figure 4.2 Height conversion factors over land. $E_0=0.3~{\rm MeV}_{\bullet}$ (Numbers on curves refer to radius of source circle in feet)




Figure 4.3 Height conversion factors over land. $E_0=0.6$ Mev. (Numbers on curves refer to radius of source circle in feet)




Figure 4.4 Height conversion factors over land. $E_0=1.2~{\rm Mev}$. (Numbers on curves refer to radius of source circle in feet)




Figure 4.5 Height conversion factors over land. $E_0=2.5~{\rm MeV}$. (Numbers on curves refer to radius of source circle in feet)




Figure 4.6 Height conversion factors over land. Spectrum I. (Numbers on curves refer to radius of source circle in feet)




Figure 4.7 Height conversion factors over land. Spectrum II. (Numbers on curves refer to radius of source circle in feet)




Figure 4.8 Height conversion factors over land. Spectrum III. (Numbers on curves refer to radius of source circle in feet)




Figure 4.9 Conversion factors from finite plane to infinite plane - monoenergetic sources.




Figure 4.10 Conversion factors from finite to infinite plane. Spectrum I, II, and III.




Figure 4.11 Height conversion factors over water - monoenergetic sources.




Figure 4.12 Height conversion factors over water. Spectrum I, II, and III.

CHAPTER 5

DISCUSSION

The purpose of this report is to provide a calculational background for the gamma-attenuation problem. The calculations represent approximate solutions to certain idealized problems which may or may not apply to practical field conditions. For example, the distribution of radioactive material on land may appear somewhat as a plane distribution, but it is probably modified by irregularities in the surface and leaching into the soil. Only accurate experimental measurements can establish the importance of such effects and, hence, introduce modifications to the calculations.

The mumerical calculations have been performed with a desk calculator and were appropriately simplified. The gross division of the energy spectrum could easily be refined by the use of more-elaborate computational equipment. The use of cubic equations to approximate the buildup curves could also be eliminated by the use of high-speed computers. However, in view of the lack of sensitivity of the results to the energy spectrum and the uncertainty in the correlation to practical situations, the curves presented in this report are probably sufficiently accurate.

REFERENCES

1. Cates, Jr., L.D., and Eisenhauer, C.; Spectral Distribution of Gamma Rays in Air; AFSWP Report No. 502A, January 1954; UNCLASSIFIED.

2. Borg, D.C., and Eisenhauer, C.; Spectrum and Attenuation of Initial Gamma Radiation from Nuclear Weapons; AFSWP Report No. 502B, January 1955; SECRET-RESTRICTED DATA.



DISTRIBUTION

Military Distribution Categories 5-40 and 5-70

		ARMY ACTIVITIES	1	+7	Director, Special Weapons Development Office, Headquarters, CONARC, Ft. Bliss, Tex. ATTN:
	ı	Asst. Dep. Chief of Staff for Military Operations,			Capt. T. E. Skinner
	_	D/A, Washington 25, D.C. ATTN: Asst. Executive (R&SW)	1	¥8	Commandant, Walter Reed Army Institute of Research, Walter Reed Army Medical Center, Washington 25, D.C.
	2	Chief of Research and Development, D/A, Washington 25, D.C. ATTN: Special Weapons and Air Defense Division	1	49.	Superintendent, U.S. Military Academy, West Point, N.Y. ATTN: Prof. of Ordnance
	3	Chief of Ordnance, D/A. Washington 25, D.C. ATTN:		50	Commandant, Chemical Corps School, Chemical Corps
4-	6	ORDIX-AR Chief Signal Officer, D/A, P&O Division, Washington			Training Command, Ft. McClellan, Ala. Commanding General, Research and Engineering Command,
	3	25, D.C. ATIN: SIGOP	51- 5	52	Army Chemical Center, Md. ATTN: Deputy for RW and
	7	The Surgeon General, D/A, Washington 25, D.C. ATTV: Chief, R&D Division			Non-Toxic Material Commanding General, Aberdeen Proving Grounds, Md.
8-		Chief Chemical Officer, D/A, Washington 25, D.C.		53	(inner envelope) ATTN: RD Control Officer (for
	10	The Quartermaster General, D/A, Washington 25, D.C. ATTN: Research and Development Div.			Director, Ballistics Research Laboratory)
11-	15	Chief of Engineers, D/A, Washington 25, D.C. ATTN:	54- !	56	Commanding General, The Engineer Center, Ft. Belvoir, Va. ATTN: Asst. Commandant, Engineer School
	16	ENGNB	:	57	Commanding Officer, Engineer Research and Development
		Chief of Transportation, Military Planning and Intelligence Div., Washington 25, D.C.			Laboratory, Ft. Belvoir, Va. ATTN: Chief, Technical Intelligence Branch
17-	19	Commanding General, Continental Army Command, Ft. Monroe, Va.	:	58	Commanding Officer, Picatinny Arsenal, Dover, N.J.
	20	President, Board #1, Headquarters, Continental Army		59	ATIN: ORDBE-TK Commanding Officer, Frankford Arsenal, Philadelphia
	21	Command, Ft. Sill, Okla. President, Board #2, Headquarters, Continental Army		(0	37, Pa. ATTN: Col. Tewes Kundel Commanding Officer, Army Medical Research Laboratory,
		Command, Ft. Knox, Ky.		60	Ft. Knox, Ky.
	22	President, Board #3, Headquarters, Continental Army Command, Ft. Benning, Ga.	61-	62	Commanding Officer, Chemical Corps Chemical and Radio- logical Laboratory, Army Chemical Center, Md. ATTN:
	23	President, Board #4, Headquarters, Continental Army			Tech. Library
	24	Command, Ft. Bliss, Tex. Commanding General, First Army, Governor's Island, New		63	Commanding Officer, Transportation R&D Station, Ft.
	25	York 4, N.Y.		64	Eustis, Va. Commandant, The Transportation School, Ft. Eustis, Va.
	25	Commanding General, Second Army, Ft. George G. Meade, Md.		-	ATTN: Security and Information Officer Director, Technical Documents Center, Evans Signal
	26	Commanding General, Third Army, Ft. McPherson, Ga.		65	Laboratory, Belmar, N.J.
	27	ATIN: ACofS, G-3 Commanding General, Fourth Army, Ft. Sam Houston, Tex.		66	Director, Waterways Experiment Station, PO Box 631, Vicksburg, Miss. ATTN: Library
	28	ATTN: G-3 Section Commanding General, Fifth Army, 1660 E. Hyde Park		67	Director, Operations Research Office, Johns Hopkins
	29	Blvd., Chicago 15. Ill.			University, 7100 Connecticut Ave., Chevy Chase, Md. Washington 15, D.C.
		Commanding General, Sixth Army, Presidio of San Fran- cisco, Calif. ATTN: AMGCT-4	68-	69	Commanding General, Quartermaster Research and Develop- ment, Command, Quartermaster Research and Development
	30	Commanding General, U.S. Army Caribbean, Ft. Amador,			Center, Natick, Mass. ATTN: CBR Liaison Officer
	31	C.Z. ATTN: Cml. Off. Commanding General, USARFANT & MDFR, Ft. Brooke,		70	Commandant, The Army Aviation School, Ft. Rucker, Ala.
	32	ruelto kico	72-	71 78	President, Board #6, CONARC, Ft. Rucker, Ala. Technical Information Service Extension, Oak Ridge,
22		Commanding General, Southern European Task Force, APO 168, New York, N.Y. ATTN: ACOfS, G-3			Tenn.
33-	34	Commander-in-Chief, Far East Command, APO 500, San Francisco, Calif. ATTN: ACofS, J-3			
	35	Commanding General, U.S. Army Forces Far Fast (Main)			NAVY ACTIVITIES
	36	APO 343, San Francisco, Calif. ATTN: ACOf5, G-3 Commanding General, U.S. Army Alaska, APO 942, Seattle,	79-	80	Chief of Naval Operations, D/N, Washington 25, D.C.
37-	28	maeq.		22	ATTN: OP-36 Chief of Naval Operations, D/N, Washington 25, D.C.
		Commanding General, U.S. Army Europe, APO 403, New York, N.Y. ATTN: OPOT Div., Combat Dev. Br.		81	ATIN: OP-03EG
39-	40	Johnshiding General, U.S. Army Pacific, APO 058, San		82	Director of Naval Intelligence, D/N, Washington 25, D.C. ATTN: OP-922V
41-	42	Commandant, Command and General Store College Et		83	Chief, Bureau of Medicine and Surgery, D/N, Washington
	43			84	25, D.C. ATTN: Special Weapons Defense Div. Chief, Bureau of Ordnance, D/N, Washington 25, D.C.
		ATIN: Library War College, Carlisle Barracks, Pa.		85	Chief of Naval Personnel, D/N, Washington 25, D.C.
	44	Commandant, The Artillery and Guided Missile School	86-	67	Chief, Bureau of Ships, D/N, Washington 25, D.C. ATTN: Code 348
	45	Secretary, The Antisiroreft Antisiroreft		88	Chief, Bureau of Yards and Docks, D/N, Washington 25,
				89	D.C. ATTN: D-140 Chief, Bureau of Supplies and Accounts, D/N, Washing-
		Combined Arms		•	ton 25, D.C.
	46	Commanding General, Army Medical Service School,	90-	92	Chief, Bureau of Aeronautics, D/N, Washington 25, D.C. Chief of Naval Research, Department of the Navy
		Brooke Army Medical Center, Ft. Sam Houston, Tex.		-	Washington 25, D.C. ATTN: Code 811
		The state of the s	阿林		A TOTAL
	_				STEED THE REAL PROPERTY OF THE PARTY OF THE
				7176	
			-	1	

MM: ASSIVE

93	Commander-in-Chief, U.S. Pacific Fleet, Fleet Post	145	Assistant Chief of Staff, Installations, Headquarters,
94	Office, San Francisco, Calif. Commander-in-Chief, U.S. Atlantic Fleet, U.S. Naval	146	USAF, Washington 25, D.C. ATTN: AFCIE-E Commander, Air Research and Development Command, PO
95- 98	Base, Norfolk 11, Va. Commandant, U.S. Marine Corps, Washington 25, D.C.	147	Box 1395, Baltimore, Md. ATTN: RDDN Commander, Air Proving Ground Command, Eglin AFB, Fla.
<i>9</i> 9 100	ATIN: Code AO3H President, U.S. Navel War College, Nevport, R.I. Superintendent, U.S. Navel Postgraduste School,	148-149 150-157	ATTN: Adj./Tech. Report Branch Director, Air University Library, Maxwell AFB, Ala. Commander, Flying Training Air Force, Waco, Tex.
101	Monterey, Calif. Commanding Officer, U.S. Naval Schools Command, U.S. Naval Station, Treasure Island, San Francisco,	158	ATTN: Director of Observer Training Commander, Crew Training Air Force, Randolph Field,
102	Calif. Commanding Officer, U.S. Fleet Training Center, Naval	159-160	Tex. ATTN: 2GTS, DCS/O Commandant, Air Force School of Aviation Medicine, Randolph AFB, Tex.
103	Base, Norfolk 11, Va. ATTN: Special Weapons School Commanding Officer, U.S. Fleet Training Center, Naval	161-163	Commander, Wright Air Development Center, Wright- Patterson AFB, Dayton, O. ATTN: WCOSI
104	Station, San Diego 36, Calif. ATTN: (SFWP School) Commanding Officer, Air Development Squadron 5, VX-5,	164-165	Commander, Air Force Cambridge Research Center, IG Hanscom Field, Bedford, Mass. ATTN: CRQST-2
105	U.S. Naval Air Station, Moffett Field, Calif. Commanding Officer, U.S. Naval Damage Control Training Center, Naval Base, Fhiladelphia 12, Pa. ATTN: ABC	166-168	AFB, N. Mex. ATTN: Library
106	Defense Course Commanding Officer, U.S. Naval Unit, Chemical Corps	169-170	Commander, Lowry AFB, Denver, Colo. ATTN: Department of Armament Training
	School, Army Chemical Training Center, Ft. McClellan, Ala.	171	Commander, 1009th Special Weapons Squadron, Head- quarters, USAF, Washington 25, D.C.
107	Commander, U.S. Naval Ordnance Laboratory, Silver Spring 19, Md. ATTN: EH	172-173	The RAND Corporation, 1700 Main Street, Santa Monica, Calif. ATTN: Nuclear Energy Division
108	Commander, U.S. Naval Ordnance Laboratory, Silver Spring 19, Md. ATTN: R	175	Commander, Second Air Force, Barksdale AFB, Louisiana. ATTN: Operations Analysis Office Commander, Eighth Air Force, Westover AFB, Mass. ATTN:
109	Commander, U.S. Naval Ordnance Test Station, Inyokern, China Lake, Calif.	176	Operations Analysis Office Commander, Fifteenth Air Force, March AFB, Calif.
110	Officer-in-Charge, U.S. Naval Civil Engineering Res. and Evaluation Lab., U.S. Naval Construction Bat-	177	ATTN: Operations Analysis Office Commander, Western Development Div. (ARDC), PO Box
111	talion Center, Port Hueneme, Calif. AFTN: Code 753 Commanding Officer, U.S. Naval Medical Research Inst., National Naval Medical Center, Betheada 14, Md.	178-184	262, Inglewood, Calif. ATTN: WEST, Mr. R. G. Weitz Technical Information Service Extension, Oak Ridge,
112	Director, U.S. Naval Research Laboratory, Washington 25, D.C. ATTN: Mrs. Katherine H. Cass		Tenn. (Surplus)
113	Director, The Material Laboratory, New York Naval Ship- yard, Brooklyn, N. Y.		OTHER DEPARTMENT OF DEFENSE ACTIVITIES
114	Commanding Officer and Director, U.S. Navy Electronics Laboratory, San Diego 52, Calif.	- 2	
115-118	Gommanding Officer, U.S. Naval Radiological Defense Laboratory, San Francisco 24, Calif. ATTN: Technical	185	Asst. Secretary of Defense, Research and Development, D/D, Washington 25, D.C. ATTN: Tech. Library
119	Information Division Commanding Officer and Director, David W. Taylor Model	186	U.S. Documents Officer, Office of the U.S. National Military Representative, SHAPE, APO 55, New York, N.Y.
120	Basin, Washington 7, D.C. ATTN: Library Commander, U.S. Naval Air Development Center, Johns- ville, Pa.	187	Director, Weapons Systems Evaluation Group, OSD, Rm 2El006, Pentagon, Washington 25, D.C.
121	Commanding Officer, Clothing Supply Office, Code ID-0, 3rd Avenue and 29th St., Brooklyn, N.Y.	188	Commandant, Armed Forces Staff College, Norfolk 11, Va. ATTN: Secretary
122	Commandant, U.S. Coast Guard, 1300 E. St. N.W., Washington 25, D.C. ATTN: Capt. J. R. Stevart	189-194	Commanding General, Field Command, Armed Forces Special Weapons Project, PO Box 5100, Albuquerque, N.
123-129	Technical Information Service Extension, Oak Ridge, Tenn. (Surplus)	195-196	Mex. Commanding General, Field Command, Armed Forces, Special Weapons Project, FO Box 5100, Albuquerque, N. Mex.
	AIR FORCE ACTIVITIES	197-201	ATTN: Technical Training Group Chief, Armed Forces Special Weapons Project, Washington 25, D.C. ATTN: Documents Library Branch
130	Asst. for Atomic Energy, Headquarters, USAF, Washington 25, D.C. ATTN: DCS/0	202-208	Technical Information Service Extension, Oak Ridge, Tenn. (Surplus)
131	Director of Operations, Headquarters, USAF, Washington 25, D.C. ATTN: Operations Analysis		
132	Director of Plans, Headquarters, USAF, Washington 25, D.C. ATTN: War Plans Div.		ATOMIC ENERGY COMMISSION ACTIVITIES
133	Director of Research and Development, Headquarters, USAF, Washington 25, D.C. ATTN: Combat Components Div.	209-211	U.S. Atomic Energy Commission, Classified Technical
134-135	Director of Intelligence, Headquarters, USAF, Washington 25, D.C. ATTN: AFOIN-IB2	212 217	Library, 1901 Constitution Ave., Washington 25, D.C. ATTN: Mrs. J. M. O'Leary (For IMA)
136	The Surgeon General, Headquarters, USAF, Washington 25, D.C. ATTN: Bio. Def. Br., Pre. Med. Div.	212-213	Los Alamos Scientific Laboratory, Report Library, PO Box 1663, Los Alamos, N. Mex. ATTN: Helen Redman Sandia Corporation, Classified Document Division,
137	Deputy Chief of Staff, Intelligence, Headquarters, U.S. Air Forces Europe, APO 633, New York, N.Y. ATTN: Directorate of Air Targets		Sandia Base, Albuquerque, N. Mex. ATTN: Martin Lucero
138	Commander, 497th Reconnaissance Technical Squadron (Augmented), APO 633, New York, N.Y.	219-221	University of California Radiation Laboratory, PO Box 808, Livermore, Calif. ATTN: Margaret Edlund
139	Commander, Far East Air Forces, APO 925, San Francisco, Calif.	222 223-264	Weapon Data Section, Technical Information Service Extension, Oak Ridge, Tenn. Technical Information Service Extension, Cak Ridge,
140	Commander-in-Chief, Strategic Air Command, Offutt Air Force Base, Omaha, Nebraska. ATTN: Special Weapons		Tenn. (Surplus)
141	Branch, Inspector Div., Inspector General Commander, Tactical Air Command, Langley AFB, Va.		ADDITIONAL DISTRIBUTION
142	ATTN: Documents Security Branch Commander, Air Defense Command, Ent AFB, Colo.	-2	
143-144	Research Directorate, Edgs. Air Force Special Weapons Center, Kirtland Air Force Base, New Mexico. ATTN: Blast Effects Research	265	Commander, 1352 Motion Picture Squadron, Lockout Mountain Laboratory, 8935 Wonderland Ave., Los Angeles 46, Calif.
	38		

Maria Residen